


RADIATION PATTERN



### FREQUENCY INDEPENDENT DATA

Description: directional stacked yagi array, triangular feed, field adjustable pattern, optional beam tilting

Frequency: 135-145 MHz, 144-156 MHz, 154-166 MHz, 163-177 MHz, 221-239 MHz, 326-353 MHz, 336-364 MHz, 365-395 MHz, 380-410 MHz, 405-440 MHz, 440-475 MHz, 830-890 MHz, 880-960 MHz

Impedance: 50 ohm

Gain: 10 dBi

H -3 dB: 173°

E -3 dB: 20°

F/B: 11 dB

Polarization: vertical

Connector: N-female / TNC-female

VSWR: < 1.5

Radome: UV resistant ABS/FG, RAL 7012, PU foam filling

Radiator: copper

Attachment: Ø 35-60 mm, aluminium alloy bracket, stainless steel V-bolts and self-locking nuts

Lightning

protection: DC-short circuited

Temperature: -40°C - +80°C

IP: 67

- combination of durability, light weight and low wind load
- radome enclosed radiator
- IP67 proof construction
- all electromechanics moulded inside of closed cell PU foam
- DC shorted feed point
- integrated impedance compensation
- integrated RF choke

**CAS3 DIRECTIONAL STACKED YAGI ARRAY**



RoHS  
Compliant

**CompleTech**

ComAnt<sup>®</sup>-antennas by CompleTech, Finland